

The LCD-XC, using our new LCD-X driver, is our first closed-back planar magnetic. Our closed design offers even greater isolation from the surrounding environment and works beautifully with portable devices.

Features and Specifications

Style	Closed-back circumaural
Transducer type	Planar magnetic
Magnetic structure	Acoustically transparent proprietary design
Magnet type	High-grade Neodymium
Transducer active diaphragm area	39.8 sq cm (6.17 sq in)
Maximum power handling	15W (for 200ms)
Sound pressure level	>130dB with 15W
Frequency response	5Hz – 20kHz extended out to 50kHz
Total harmonic distortion	<1% through entire frequency range
Impedance	Purely resistive 22ohm
Efficiency	95dB/1mW
Optimal power requirement	1-4W

Package Includes

- 2.5m (8.2ft) 6.35mm (1/4in) to dual 4-pin mini-XLR cable
- 6.35mm (1/4in) to 3.5mm (1/8in) stereo adapter
- Wood care kit
- Ruggedized travel case
- Warranty documents

Accessories

- 2.5m (8.2ft) 4-pin XLR to dual 4-pin mini-XLR cable
- 4-pin to dual 3-pin XLR adapter
- · Extended yoke rods
- Leather care kit
- · Wooden show case

Options

- · Lambskin or leather-free headband and earpads
- Enclosure available in various anodized aluminum finishes
- Cups available in a variety of premium woods

\$1,799

Other Models



LCD-3 Ultra high-performance \$1,945



LCD-2 High-performance \$1,145



LCD-X Reference-level \$1,699